
APPLICATION FOR CERTIFICATE OF APPROPRIATENESS (COA)
Building address 702 & 4th st. Bethlehem PA 18015
Owner of building John G1055 Phone
Owner's email & mailing address
Applicant Francisco J Lopez Phone
Applicant's email & mailing address
Street and Number City State Zip Code
APPLICANT MUST ATTEND MEETING FOR CASE TO BE HEARD.
USE THE CHECKLIST ON THE BACK OF THIS APPLICATION TO ENSURE YOUR SUBMISSION IS
<u>COMPLETE.</u>
Historic & Architectural Review Board – Application form, photographs, and drawings must be submitted by 12:00 Noon on the last Wednesday of the month in order to be placed on the agenda for the next meeting.
South Bethlehem & Mount Airy Historic Conservation Commission - Application form, photographs, and drawings must be
submitted by 12:00 noon on the second Monday of the month in order to be placed on the agenda for the next meeting.
1. PHOTOGRAPHS - Photographs of your building and neighboring buildings must accompany your application.
2. TYPE OF WORK PROPOSED – Check all that apply. Please bring any samples or manufactures specifications for
products you will use in this project.
Trim and decorative woodwork Skylights
Siding and Masonry Metal work
Roofing, gutter and downspout Light fixtures
Windows, doors, and associated hardware Signs
Storm windows and storm doors Demolition
Shutters and associated hardware Other
Paint (Submit color chips – HARB only)
2. DRAWINGS OF PROPOSED WORK 20 1111
3. DRAWINGS OF PROPOSED WORK – Required drawings <u>must accompany</u> your application. Please submit <u>ONE</u>
ORIGINAL AND TEN (10) COPIES OF DRAWINGS, PHOTOGRAPHS, APPLICATION FORM, AND ANY
<u>SPECIFICATIONS</u>
Alteration, renovation, restoration (1/4 or 1/8"=1'0" scale drawings required IF walls or openings altered.)
New addition (1/4" or 1/8"=1'0" scale drawings: elevations, floor plans, site plan)
New building or structure (1/4" or 1/8"=1'0" scale drawings: elevations, floor plans, site plan)
Demolition, removal of building features or building (1/4" or 1/8"=1'0" scale drawings: elevation of remaining site
and site plan)
A scale drawing, with an elevation view, is required for all sign submittals
4. DESCRIBE PROJECT - Describe any work checked in #2 and #3 above. Attach additional sheets as needed
4. DESCRIBE PROJECT - Describe any work checked in #2 and #3 above. Attach additional sheets as needed. Remove slate. Replaced with architectural shinglis.
ment sure sure sure sure sure sure sure sure
5. APPLICANT'S SIGNATURE Francisco J Long DATE: 5-30-18
DATE: JULIO

PRODUCT INFORMATION SHEET Timberline HD® Shinales

Made To Protect Your Home. Your Story. And Those Of Over 50 Million Of Your Fellow North Americans!





PRODUCT INFORMATION

"Value and performance in a genuine wood-shake look"

Timberline HD® Shingles Provide These Unique Benefits:

- Dimensional Look . . . Features GAF's proprietary color blends and enhanced shadow effect for a genuine wood-shake
- Highest Fire Rating . . . Class A fire rating from Underwriters Laboratories
- High Performance . . . Designed with Advanced Protection® Shingle Technology, which reduces the use of natural resources while providing excellent protection for your home (visit gaf.com/aps to learn more)
- Stays In Place . . . Dura Grip™ Adhesive seals each shingle tightly and reduces the risk of shingle blow-off. Shingles warranted to withstand winds up to 130 mph (209 km/h).1
- Peace Of Mind . . . Lifetime Itd. transferable warranty with Smart Choice® Protection (non-prorated material and installation labor coverage) for the first ten years2
- Perfect Finishing Touch . . . Use Timbertex® Premium Ridge Cap Shingles or Ridglass® Premium Ridge Cap Shingles³

COLORS/AVAILABILITY

- COLORS: Barkwood, Birchwood, Biscayne Blue, Canadian Driftwood, Charcoal, Copper Canyon, Driftwood, Fox Hollow Gray, Golden Amber, Hickory, Hunter Green, Mission Brown, Oyster Gray, Patriot Red, Pewter Gray, Shakewood, Slate, Sunset Brick, Weathered Wood, White, and Williamsburg Slate
- REGIONAL AVAILABILITY: Northeast, Southeast, Southwest, West, and Central Areas

¹This wind speed coverage requires special installation; see GAF Shingle & Accessory Ltd. Warranty for details.

²See GAF Shingle & Accessory Ltd. Warranty for complete coverage and restrictions. The word "Lifetime" refers to the length of coverage provided by the GAF Shingle & Accessory Ltd. Warranty and means as long as the original individual owner(s) of a single-family detached residence [or the second owner(s) in certain circumstances] owns the property where the shingles are installed. For owners/structures not meeting the above criteria, Lifetime coverage is not applicable. ³These products are not available in all areas. See <u>www.gaf.com/ridgecapavailability</u> for details.

See http://www.gaf.com/Roofing/Residential/Products/Shingles/Timberline/High_Definition for color availability in your area

APPLICABLE STANDARDS & PROTOCOLS

- UL 790, Class A
- Miami-Dade County Product Control Approved 130419.04 (Location dependent; contact Technical Services at 800.766.3411)
- Florida Building Code Approved FL10124-R12
- UL 997 modified to 110 mph
- ASTM D7158, Class H
- ASTM D3161, Class F
- ASTM D3018, Type 1

- ASTM D3462
- ICC ESR-1475, ESR-3267
- Texas Department of Insurance
- CSA A123.5^{***}
- ENERGY STAR[®] Qualified (White Only) (U.S. Only)
- Title 24 Compliant, CRRC Listed, and Meets Los Angeles Green Building Code (Birchwood, Copper Canyon, Golden Amber, and White Only)

Effective 7/1/08, existing NYC MEA's may be used but are no longer required.

PRODUCT/SYSTEM SPECIFICS+

- · Fiberglass Asphalt Construction
- Dimensions (approx.): 13 1/4" x 39 3/8" (337 x 1,000 mm)
- Exposure: 5 5/8" (143 mm)
- Bundles/Square: 3
 Biogga/Square: 64
- Pieces/Square: 64
- Nails/Square: 256 (384 where 6 nails per shingle is required)^{††}
- StainGuard® Protection: Yes (Location dependent; contact Technical Services at 800.766.3411)
- Hip/Ridge: Timbertex[®]; Seal-A-Ridge[®]; Z[®] Ridge; Ridglass[®] 8"; Ridglass[®] 10"
- Starter: ProStart[®] & WeatherBlocker[™]

INSTALLATION

Detailed installation instructions are provided on the inside of each bundle wrapper of Timberline HD[®] Shingles. Installation instructions may also be obtained at www.gaf.com.

[&]quot;Obtained ESR 3267 evaluation from ICC Evaluation Services based on compliance with the requirements of AC438, an acceptance criteria established by ICC Evaluation Services to evaluate asphalt shingles that contains performance tests in addition to those required by the building code. (ICC Evaluation Services provides technical evaluations of building products that directly address the issue of code compliance. Building inspectors use these evaluation reports to help determine code compliance and enforce building regulations.)
"Refers to shingles sold in Canada only.

[†]Refer to complete published installation instructions.

^{**}Required by some local codes and required for enhanced wind coverage on certain products.

